

Pro Peel

Product code G4602

Formerly known as Gramos Product Code 6112.

Solvent based peelable coating



PRODUCT DESCRIPTION

PROPEEL is a white pigmented temporary protective coating designed for application to all smooth, clean, metal spray booth walls in order to provide an easy method of booth maintenance. The dried film is readily peelable and enables even heavy overspray deposits to be quickly and cleanly removed.

Exposed areas can then be touched in or the entire area re-sprayed as necessary. By providing a white, light reflective surface better working conditions are obtained making for a consistent achievement of high quality work.

FEATURES & BENEFITS

- * Strong easily peelable film.
- * Enables heavy overspray to be removed quickly and cleanly.
- * Light reflective surface for better working conditions.
- * Reduces maintenance time.
- * Heavily contaminated areas may be cut and painted in.

DIRECTIONS FOR USE

Use as supplied, stirring thoroughly before use to disperse any settled pigment.

Apply by conventional spraying techniques using normal pressure spraying equipment, pot pressure 20psi (1-2 bar), air pressure 40-60psi (3-4 bar); and using a 70 thou (1.78mm) tip, with appropriate air cap and needle.

Apply a double pass, wet on wet, to give a dense white film. Do not dry spray as this may lead to some film shrinkage and poor peelability.

Do not use suction feed guns.

Do not apply to painted or plastic surfaces.

After use clean all equipment with 6118 THINNERS

COVERAGE

2-3 square metres/litre, at 2-3thou (0.05-0.076mm) dry film thickness.

SPECIAL STORAGE

Store in a cool place in compliance with Petroleum Consolidation Act 1928 and Amendments, or Local/National Highly Flammable Liquids Regulations.

Protect from freezing.

GRAMOS APPLIED LTD

Spring Road, Smethwick, West Midlands. B66 1PT.

Tel: 0121 525 4000 / 0121 524 1000 Fax: 0121 525 4950 / 0121 525 4919

E-mail: info@gramos-applied.com website: www.gramos-applied.com

All recommendations made and information supplied are to assist customers, they do not infer any legal warranty or liability.

Printed in the UK. 11/2003

Issue No. 1

Page 1 of 2

Pro Peel

WARNING

Solvent based peelable coatings are not generally suitable for application to painted, plastic, or lacquered surfaces, and **MUST** be carefully patch tested before use to ensure no surface attack occurs and the product remains easily peelable after normal usage conditions.

Any use of these products on solvent sensitive surfaces where natural evaporation of the solvent may be retarded can lead to aggravated solvent attack, for instance, seepage under a mask.

HEALTH AND SAFETY INFORMATION – SEE SEPARATE HEALTH AND SAFETY SHEET

GRAMOS APPLIED LTD

Spring Road, Smethwick, West Midlands. B66 1PT.
Tel: 0121 525 4000 / 0121 524 1000 Fax: 0121 525 4950 / 0121 525 4919
E-mail: info@gramos-applied.com website: www.gramos-applied.com

All recommendations made and information supplied are to assist customers, they do not infer any legal warranty or liability.
Printed in the UK. 11/2003 Issue No. 1 Page 2 of 2